



**DLI100 10' REMOTE SANDWICH SPECIFICATIONS:**

REFRIGERATION  
LOAD: 9450 BTU/hr  
SUCTION TEMP: 20° F  
LIQUID LINE: 3/8IN ODS  
SUCTION LINE: 5/8IN ODS

ELECTRICAL 115VAC, 60HZ, 1PH.  
EVAP. FANS: 3.12A  
LIGHT BALLAST: 1.5A  
TOTAL: 4.62A

**DLI100 10' REMOTE SANDWICH REFRIGERATED REAR STORAGE SPECIFICATIONS:**

REFRIGERATION  
LOAD: 4000 BTU/hr  
SUCTION TEMP: 20° F  
LIQUID LINE: 3/8IN ODS  
SUCTION LINE: 3/8IN ODS

ELECTRICAL 115VAC, 60HZ, 1PH.  
EVAP. FANS: 3.00A  
TOTAL: 3.00A

börger systems

SCALE: 1:20

**DLI100 SERIES**

DRAWN BY: DWT

DATE: 10-21-03

**DLI100 - 10PH**

CHECKED BY:

**10' REMOTE SANDWICH / FOOD PREP**

DATE REV. DIM: INCH

DRAWING NUMBER

REVISION TOL: ±1/32

**P4257A**