



CASE SPECIFICATIONS:

REFRIGERATION
 LOAD: 4,580 BTU/hr
 SUCTION TEMP: 20° F
 LIQUID LINE: 3/8IN ODS
 SUCTION LINE: 5/8IN ODS

ELECTRICAL 115VAC, 60HZ, 1PH.
 EVAP. FANS: 2.54A, MCA 15A
 LIGHT BALLAST: 1.5A, MCA 15A

ADDITIONAL CONNECTIONS FOR:

LIQUID LINE SOLENOID VALVE
 DISCHARGE AIR PROBE
 REAR FAN CONTROL RELAY

- NOTES:**
1. OPTIONS NOT SHOWN ON DRAWING SHOULD BE LISTED IN WRITTEN PROPOSAL AND LISTED ON PURCHASE ORDER.
 2. ELEC. CONNECTION: 115V/230V, 4x4 SUPPLY BOX AS NEEDED.
 3. EXPANSION VALVES: SPORLAN "Q" SERIES STANDARD UNLESS OTHERWISE SPECIFIED.
 4. DEFROST CONTROL: REMOTE CASES (N/A, DIGITAL CASE CONTROLLERS AVAILABLE), OPTIONAL CONDENSING UNIT (DIGITAL CASE CONTROLLER).
 5. THERMOSTATS & LIQUID LINE SOLENOID VALVES: OPTIONAL.
 6. DRAIN: 1 1/2 INCH PVC.
 7. SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.

börger systems

SCALE: 1:X		DRAWN BY: DWT	
DATE: 03/18/05		CHECKED BY: DWT	
4' FOOD LOW DOMED BG4LD			
DATE	REV.	DIM:	DRAWING NUMBER
REVISION		TOL: ±1/32	4639A