

CASE SPECIFICATIONS:

REFRIGERATION

LOAD: 3,600 BTU/hr
 SUCTION TEMP: -20° F
 LIQUID LINE: 3/8IN ODS
 SUCTION LINE: 5/8IN ODS

ELECTRICAL 115VAC, 60HZ, 1PH.


EVAP. FANS: 1.8A
 LIGHT BALLAST: 1.95A
 DOOR HEATER: 5.23A
 TOTAL: 8.98A
 MCA: 15.0A

ELECTRICAL 208VAC, 60HZ, 1PH.

DEFROST HEATER: 5.2A
 TOTAL: 5.2A
 MCA: 15.0A

NOTES:

1. OPTIONS NOT SHOWN ON DRAWING SHOULD BE LISTED IN WRITTEN PROPOSAL AND LISTED ON PURCHASE ORDER.
2. ELEC. CONNECTION: 115V/230V, 4x4 SUPPLY BOX AS NEEDED.
3. EXPANSION VALVES: SPORLAN "Q" SERIES STANDARD UNLESS OTHERWISE SPECIFIED.
4. DEFROST CONTROL: REMOTE CASES (N/A, DIGITAL CASE CONTROLLERS AVAILABLE), OPTIONAL CONDENSING UNIT (DIGITAL CASE CONTROLLER).
5. THERMOSTATS & LIQUID LINE SOLENOID VALVES: OPTIONAL.
6. DRAIN: 1 1/2 INCH PVC.
7. SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.

AUTHORIZATION (PRINT):	DATE:	 börger systems		SCALE: 1:16	DRAWN BY: D HUNT
SIGNATURE:				DATE: 6-8-05	CHECKED BY:
		6-27-05	DRH	4' FREEZER ANGLE FRONT BG4FS	
DATE	REV.	DWG:	INCH	DRAWING NUMBER	
REVISION	TOL:			P4656A	