

REFRIGERATION:
 18,370 BTU/hr @ 20°F
 ø1/2IN ODS LIQUID.
 ø7/8IN ODS SUCTION.

TOP AREA: 164 SQR FEET.


ELECT. LOADS: 115V, 6.04A, 60HZ, 1PH.
 ALL ELECT LOADS MAXIMUM AND INCLUDE THE FOLLOWING:
 (6) MERCH. BALLASTS 4.44A, (2) STORAGE BALLAST 1.6A

WALKIN COOLER INFORMATION:
 (1) LIGHT SWITCH ADJACENT SERVICE DOOR HANDLE.
 (1) THERMOMETER ABOVE LIGHT SWITCH.
 (1) VENT ABOVE THE SERVICE DOOR.

DISPLAY IN FORMATION:
 (9) BACK PANELS ON THE DIVIDING WALL ARE HINGED FOR REAR STOCKING.
 (27) TEMPERED GLASS SHELVES ARE HIEGHT ADJUSTABLE.

NOTES:

1. OPTIONS NOT SHOWN ON DRAWING SHOULD BE LISTED IN WRITTEN PROPOSAL AND LISTED ON PURCHASE ORDER.
2. ELEC. CONNECTION: 115V/230V, 4x4 SUPPLY BOX AS NEEDED.
3. EXPANSION VALVES: SPORLAN "Q" SERIES STANDARD UNLESS OTHERWISE SPECIFIED.
4. DEFROST CONTROL: REMOTE CASES (N/A, DIGITAL CASE CONTROLLERS AVAILABLE), OPTIONAL CONDENSING UNIT (DIGITAL CASE CONTROLLER).
5. THERMOSTATS & LIQUID LINE SOLENOID VALVES: OPTIONAL.
6. DRAIN: 1 INCH NATIONAL PIPE STRAIGHT THREAD.
7. SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.

		 börger systems	
	SCALE: 1:24	DRAWN BY: D HUNT	
	DATE: 6-16-04	CHECKED BY:	
10DR WOD WRAP (1DR NON-OPN)			
DATE	REV.	DWG. INCH	DRAWING NUMBER
REVISION	TOL:		P4467B