

CASE SPECIFICATIONS:


REFRIGERATION
 DOORED: 2,875 BTU/hr
 OPEN: 3,900 BTU/hr
 TOTAL: 6,775 BTU/hr
 SUCTION TEMP: 20° F
 LIQUID LINE: 3/8IN ODS
 SUCTION LINE: 5/8IN ODS

ELECTRICAL 115VAC, 60HZ, 1PH.
 EVAP. FANS: .39A
 LIGHT BALLAST: 1.48A
 COND. PUMP: 1.0A
 TOTAL: 2.87A
 MCA: 15.0A

ELECTRICAL 208-230VAC, 60HZ, 1PH.
 COND. PAN: 7.2A
 1HP COND. UNIT: 7.7A
 TOTAL: 14.9A
 MCA: 18.0A

NOTES:

1. OPTIONS NOT SHOWN ON DRAWING SHOULD BE LISTED IN WRITTEN PROPOSAL AND LISTED ON PURCHASE ORDER.
2. ELEC. CONNECTION: 115V/230V, 4x4 SUPPLY BOX AS NEEDED.
3. EXPANSION VALVES: SPORLAN "Q" SERIES STANDARD UNLESS OTHERWISE SPECIFIED.
4. DEFROST CONTROL: REMOTE CASES (N/A, DIGITAL CASE CONTROLLERS AVAILABLE), OPTIONAL CONDENSING UNIT (DIGITAL CASE CONTROLLER).
5. THERMOSTATS & LIQUID LINE SOLENOID VALVES: OPTIONAL.
6. DRAIN: 1 1/2 INCH PVC.
7. SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.

AUTHORIZATION (PRINT):	DATE:					 börger systems						
SIGNATURE:							SCALE: 1:24	DRAWN BY: D HUNT				
						DATE: 4-14-05	CHECKED BY:					
						2DR 3FT DF COMBO						DRAWING NUMBER
						DATE	REV.	DIM:	INCH	P4647A		
REVISION	TOL:											