

SHELF SPECIFICATIONS:

- (8) CONVERTABLE SHELVES FOR ARRANGEMENTS
- (35) 10 INCH FLORALWARE VASES

CASE SPECIFICATIONS:

REFRIGERATION


LOAD: 14,030 BTU/hr  
 SUCTION TEMP: 20° F  
 LIQUID LINE: 3/8IN ODS  
 SUCTION LINE: 5/8IN ODS

ELECTRICAL 115VAC, 60HZ, 1PH.

EVAP. FANS: .39A  
 LIGHT BALLAST: 1.48A  
 FLOOD LIGHTS: 2.2A  
 TOTAL: 4.07A  
 MCA: 15.0A

NOTES:

1. OPTIONS NOT SHOWN ON DRAWING SHOULD BE LISTED IN WRITTEN PROPOSAL AND LISTED ON PURCHASE ORDER.
2. ELEC. CONNECTION: 115V/230V, 4x4 SUPPLY BOX AS NEEDED.
3. EXPANSION VALVES: SPORLAN "Q" SERIES STANDARD UNLESS OTHERWISE SPECIFIED.
4. DEFROST CONTROL: REMOTE CASES (N/A, DIGITAL CASE CONTROLLERS AVAILABLE), OPTIONAL CONDENSING UNIT (DIGITAL CASE CONTROLLER).
5. THERMOSTATS & LIQUID LINE SOLENOID VALVES: OPTIONAL.
6. DRAIN: 1 1/2 INCH PVC.
7. SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.

AUTHORIZATION (PRINT):	DATE:					 börger systems	
SIGNATURE:						SCALE: 1:24	DRAWN BY: D HUNT
						DATE: 1-25-05	CHECKED BY:
						3 x 2 WRAP RIGHT AUX SHELVES	
						DATE REV. DIM: INCH	DRAWING NUMBER
					REVISION	TOL:	P4616A