


CASE SPECIFICATIONS
 AREA: 116.7 SQ FT

REFRIGERATION:
 LOAD: 16,200 BTU/hr
 SUCTION TEMP: 20°F
 LIQUID LINE: 3/8IN ODS
 SUCTION LINE: 7/8IN ODS

ELECTRICAL 115VAC 60HZ, 1PH
 EVAP FANS: 5.5A
 MRECH. LIGHTS: 7.2A
 TROFFER LIGHTS: 2.82A
 TOTAL: 14.58A

NOTES:

1. OPTIONS NOT SHOWN ON DRAWING SHOULD BE LISTED IN WRITTEN PROPOSAL AND LISTED ON PURCHASE ORDER.
2. ELEC. CONNECTION: 115V/230V, 4x4 SUPPLY BOX AS NEEDED.
3. EXPANSION VALVES: SPORLAN "Q" SERIES STANDARD UNLESS OTHERWISE SPECIFIED.
4. DEFROST CONTROL: REMOTE CASES (N/A, DIGITAL CASE CONTROLLERS AVAILABLE), OPTIONAL CONDENSING UNIT (DIGITAL CASE CONTROLLER).
5. THERMOSTATS & LIQUID LINE SOLENOID VALVES: OPTIONAL.
6. DRAIN: 1 1/2 INCH PVC.
7. SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.

AUTHORIZATION (PRINT):	DATE:			 börger systems	
SIGNATURE:					SCALE: 1:48
				DATE: 11-13-98	CHECKED BY:
		10-7-06	DRH	6DR WOD W/2BTD	
		DATE	REV.	DIM: INCH	DRAWING NUMBER
		REVISION	TOL:		P2866A