

**CASE SPECIFICATIONS:**


**REFRIGERATION**

LOAD: 5,027 BTU/hr  
 SUCTION TEMP: 20° F  
 LIQUID LINE: 3/8IN ODS  
 SUCTION LINE: 5/8IN ODS

**ELECTRICAL** 115VAC, 60HZ, 1PH.  
 EVAP. FANS: .13A  
 TOTAL: .13A

**NOTES:**

1. OPTIONS NOT SHOWN ON DRAWING SHOULD BE LISTED IN WRITTEN PROPOSAL AND LISTED ON PURCHASE ORDER.
2. ELEC. CONNECTION: 115V/230V, 4x4 SUPPLY BOX AS NEEDED.
3. EXPANSION VALVES: SPORLAN "Q" SERIES STANDARD UNLESS OTHERWISE SPECIFIED.
4. DEFROST CONTROL: REMOTE CASES (N/A, DIGITAL CASE CONTROLLERS AVAILABLE), OPTIONAL CONDENSING UNIT (DIGITAL CASE CONTROLLER).
5. THERMOSTATS & LIQUID LINE SOLENOID VALVES: OPTIONAL.
6. DRAIN: 1 INCH NATIONAL PIPE STRAIGHT THREAD.
7. SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.

		 <b>börger systems</b>	
SCALE:	1:12	DRAWN BY: D HUNT	
DATE:	7-14-03	CHECKED BY:	
4FT HP LPM			
DATE	REV.	DIM:	INCH
REVISION		TOL:	
			DRAWING NUMBER <b>P3094B</b>