

CASE SPECIFICATIONS: TOP AREA: 143.3 SQR FT

REFRIGERATION LOAD: 15,800 BTU/hr
 COIL: CTA 46-190
 SUCTION TEMP: 20° F
 LIQUID: 3/8IN ODS
 SUCTION: 7/8IN ODS


ELECTRICAL 115VAC, 60HZ, 1PH.
 EVAP. FANS: 4.4A
 MERCH. LIGHTS: 2.82A
 STORAGE LIGHTS: 1.6A
 TOTAL: 8.82A

WALIN COOLER INFORMATION:
 LIGHT SWITCH ADJACENT SERVICE DOOR.
 THERMOMETER ABOVE LIGHT SWITCH.
 VENT ABOVE THE SERVICE DOOR.

DISPLAY INFORMATION!
 BACK GLASS PANELS ON DIVIDING WALL ARE
 HINGED FOR REAR STOCKING.
 TEMERED GLASS SHELVES ARE HEIGHT ADJUSTABLE.
 ENDS OF THE DISPLAY AREA ARE ENCLOSED
 WITH METAL DIVIDERS.

NOTES:

1. OPTIONS NOT SHOWN ON DRAWING SHOULD BE LISTED IN WRITTEN PROPOSAL AND LISTED ON PURCHASE ORDER.
2. ELEC. CONNECTION: 115V/230V, 4x4 SUPPLY BOX AS NEEDED.
3. EXPANSION VALVES: SPORLAN "Q" SERIES STANDARD UNLESS OTHERWISE SPECIFIED.
4. DEFROST CONTROL: REMOTE CASES (N/A, DIGITAL CASE CONTROLERS AVAILABLE), OPTIONAL CONDENSING UNIT (DIGITAL CASE CONTROLER).
5. THERMOSTATS & LIQUID LINE SOLENOID VALVES: OPTIONAL.
6. DRAIN: 1 1/2 INCH PVC.
7. SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.

AUTHORIZATION (PRINT):	DATE:	 börger systems		DRAWN BY: D HUNT
SIGNATURE:				SCALE: 1:32
		DATE: 6/19/06	5DR 2BAY WOD	
DATE	REV.	DIM:	INCH	DRAWING NUMBER
REVISION		TOL:		P4868A