

CASE SPECIFICATIONS:


REFRIGERATION
LOAD: 6,900 BTU/hr
SUCTION TEMP: 20° F
LIQUID LINE: 3/8IN ODS
SUCTION LINE: 5/8IN ODS

ELECTRICAL 115VAC, 60HZ, 1PH.
EVAP. FANS: .26A
LIGHT BALLAST: 2.82A
CONDENSATE PUMP: 1.0A
EVAP. PAN: 3.0A
TOTAL: 7.08A
MCA: 15.0A

ELECTRICAL 230VAC, 60HZ, 1PH.
1HP COND. UNIT: 10.9A
TOTAL: 7.7A
MCA: 10.8A

NOTES:

1. OPTIONS NOT SHOWN ON DRAWING SHOULD BE LISTED IN WRITTEN PROPOSAL AND LISTED ON PURCHASE ORDER.
2. ELEC. CONNECTION: 115V/230V, 4x4 SUPPLY BOX AS NEEDED.
3. EXPANSION VALVES: SPORLAN "Q" SERIES STANDARD UNLESS OTHERWISE SPECIFIED.
4. DEFROST CONTROL: REMOTE CASES (N/A, DIGITAL CASE CONTROLLERS AVAILABLE), OPTIONAL CONDENSING UNIT (DIGITAL CASE CONTROLLER).
5. THERMOSTATS & LIQUID LINE SOLENOID VALVES: OPTIONAL.
6. DRAIN: 1 INCH NATIONAL PIPE STRAIGHT THREAD.
7. SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.

		 börger systems	
		SCALE: 1:24	DRAWN BY: D HUNT
		DATE: 9-14-99	CHECKED BY:
8-24-04 DRH		5DR 2BAY ECP	
DATE	REV.	DIM: INCH	DRAWING NUMBER
REVISION	TOL:		P3152B