



CASE SPECIFICATIONS:

REFRIGERATION
 LOAD: 12,960 BTU/hr
 SUCTION TEMP: 20° F
 LIQUID LINE: 3/8IN ODS
 SUCTION LINE: 5/8IN ODS

ELECTRICAL 115V, 60HZ, 1PH.
 EVAP. FANS: 1.44A
 LIGHT BALLASTS: 1.15A
 TOTAL: 2.59A

CASE SPECIFICATIONS (DOORS):

REFRIGERATION
 LOAD: 4050 BTU/hr
 SUCTION TEMP: 20° F
 LIQUID LINE: 3/8IN ODS
 SUCTION LINE: 5/8IN ODS

ELECTRICAL 115V, 60HZ, 1PH.
 EVAP. FANS: .72A
 LIGHT BALLASTS: 1.15A
 TOTAL: 1.87A

NOTES:

1. DOORS: LEFT HAND HINGED STANDARD. RIGHT HAND OPTIONAL. (NO HEATERS REQ'D).
2. LIGHTS: HIGH OUTPUT/COOL WHITE STANDARD. SPX35 AVAIL. IN LIMITED BULB LENGTHS.
3. ELEC. CONNECTION: TOP MOUNTED 115V/230V, 4X4 SUPPLY BOX AS NEEDED.
4. REFG: R22 STANDARD UNLESS OTHERWISE SPEC. (STUBBED OUT TOP/REAR OF CASE).
5. COMPUTERIZED CASE CONTROLLERS: OPTIONAL.
6. EXPANSION VALVES: SPORLAN "Q" SERIES STANDARD UNLESS OTHERWISE SPECIFIED.
7. DEFROST CONTROL: RMT. CASE (N/A). OPTIONAL C.U. (PRESSURE CONTROL SWITCH).
8. THERMOSTATS & LIQUID LINE SOLENOID VALVES: OPTIONAL.
9. SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.

börger systems			
SCALE:	1:16	DRAWN BY: A. BESIC	
DATE:	5-02-01	CHECKED BY:	
12FT DOORS ABOVE OPEN			
DATE:	REV.	DIM:	INCHES
REVISION		TOL:	±1/4
			DRAWING NUMBER P3754B