


CASE SPECIFICATIONS:

REFRIGERATION GLYCOL
LOAD: 17,900 BTU/hr
GLYCOL TEMP: 20F
%G CON: 35
GPM: 2.2
PRES. DROP: 4.2
LINE: 7/8IN ODS

ELECTRICAL 115VAC, 60HZ, 1PH.
EVAP. FANS: .91A
LIGHT BALLAST: 3.5A
TOTAL: 4.41A

NOTES:

1. OPTIONS NOT SHOWN ON DRAWING SHOULD BE LISTED IN WRITTEN PROPOSAL AND LISTED ON PURCHASE ORDER.
2. ELEC. CONNECTION: 115V/230V, 4x4 SUPPLY BOX AS NEEDED.
3. EXPANSION VALVES: SPORLAN "Q" SERIES STANDARD UNLESS OTHERWISE SPECIFIED.
4. DEFROST CONTROL: REMOTE CASES (N/A, DIGITAL CASE CONTROLLERS AVAILABLE), OPTIONAL CONDENSING UNIT (DIGITAL CASE CONTROLLER).
5. THERMOSTATS & LIQUID LINE SOLENOID VALVES: OPTIONAL.
6. DRAIN: 1 INCH NATIONAL PIPE STRAIGHT THREAD.
7. SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.

		 börger systems	
		SCALE: 1:24	DRAWN BY: D HUNT
		DATE: 1-13-04	CHECKED BY:
1-20-04 DRH		7DR, 9.5 x 1.5FT HUTCH	
DATE	REV.	DIM: INCH	DRAWING NUMBER
REVISION	TOL:		P4331B