

CASE SPECIFICATIONS:

REFRIGERATION: PER SECTION
 8FT SECT: 8,000 BTU/hr
 "U" SECT: 16,000 BTU/hr
 SUCTION TEMP: 20° F
 LIQUID LINE: 3/8IN ODS
 SUCTION LINE: 5/8IN ODS

ELECTRICAL 115VAC, 60HZ, 1PH.
 EVAP. FANS: .52A
 LIGHT BALLAST: 3.5A
 CASE TOTAL: 4.02A
 MCA: 15.0A

6FT PLUG MOLD W/10 OUTLETS
 ON NON_POWER CABINET

OPTIONAL POWER CABINET SPECIFICATIONS:


COND. PUMPS: 2.0A (OPTIONAL)
 TOTAL: 2.0A
 MCA: 15.0A

ELECTRICAL 230VAC, 60HZ, 1PH.
 EVAP. PAN: 6.5A (OPTIONAL)
 3HP COND. UNIT: 15.57A (OPTIONAL)

TOTAL: 22.07A
 MCA: 35.4A

NOTES:

1. OPTIONS NOT SHOWN ON DRAWING SHOULD BE STATED IN WRITTEN PROPOSAL AND LISTED ON PURCHASE ORDER.
2. ELECTRICAL CONNECTION: 115V/230V, 4X4 SUPPLY BOX AS NEEDED.
3. EXPANSION VALVES: SPORLAN "Q" SERIES STANDARD UNLESS OTHERWISE SPECIFIED.
4. DEFROST CONTROL: REMOTE CASES (N/A, DIGITAL CASE CONTROLLERS AVAILABLE), OPTIONAL CONDENSING UNIT (DIGITAL CASE CONTROLLER).
5. THERMOSTATS & LIQUID LINE SOLENOID VALVES: OPTIONAL.
6. DRAIN: STRAINER BASKET W/TRAP TO 1 1/2 INCH PVC.
7. SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.

| | | | | | |
|----------|------|---|--|-----------------------|------------------|
| | |  | | börger systems | |
| | | SCALE: 1:30 | | | DRAWN BY: D HUNT |
| | | DATE: 10-1-03 | | | CHECKED BY: NAME |
| 8-10-04 | DRH | 8 X 24 E (LPM EFFICIENCY) | | | |
| DATE | REV. | DIM: INCH | | | DRAWING NUMBER |
| REVISION | TOL: | | | P4240B | |