


CASE SPECIFICATIONS:

REFRIGERATION  
 LOAD: 3,036 BTU/hr  
 SUCTION TEMP: 30° F  
 LIQUID LINE: 3/8IN ODS  
 SUCTION LINE: 5/8IN ODS

ELECTRICAL 115VAC, 60HZ, 1PH.  
 EVAP. FANS: .13A  
 LIGHT BALLAST: .94A  
 CONDENSATE PUMP: 1.0A  
 EVAP. PAN: 3.0A  
 1/2HP COND. UNIT: 9.2A  
 TOTAL: 14.27A  
 MCA: 17.4A

NOTES:

1. OPTIONS NOT SHOWN ON DRAWING SHOULD BE LISTED IN WRITTEN PROPOSAL AND LISTED ON PURCHASE ORDER.
2. ELEC. CONNECTION: 115V/230V, 4x4 SUPPLY BOX AS NEEDED.
3. EXPANSION VALVES: SPORLAN "Q" SERIES STANDARD UNLESS OTHERWISE SPECIFIED.
4. DEFROST CONTROL: REMOTE CASES (N/A, DIGITAL CASE CONTROLLERS AVAILABLE), OPTIONAL CONDENSING UNIT (DIGITAL CASE CONTROLLER).
5. THERMOSTATS & LIQUID LINE SOLENOID VALVES: OPTIONAL.
6. DRAIN: 1 INCH NATIONAL PIPE STRAIGHT THREAD.
7. SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.

		 <b>börger systems</b>	
		SCALE: 1:16	DRAWN BY: D HUNT
		DATE: 6-1-00	CHECKED BY:
9-22-04 DRH		2DR 2BAY WINE	
DATE	REV.	DIM: INCH	DRAWING NUMBER
REVISION	TOL:		P3437B