



CASE SPECIFICATIONS:

REFRIGERATION  
 LOAD: 10,350 BTU/hr  
 SUCTION TEMP: 20° F  
 LIQUID LINE: 3/8IN ODS  
 SUCTION LINE: 5/8IN ODS

ELECTRICAL 115V, 60HZ, 1PH.  
 EVAP. FANS: 8.8A  
 LIGHT BALLASTS: 6.3A  
 TOTAL: 15.1A

ELECTRICAL 230V, 60HZ, 1PH.  
**REMOTE OUTSIDE LOCATED**  
 1 1/2HP COND. UNIT: 16.3A  
 TOTAL: 16.3A

NOTES:

1. DOORS: LEFT HAND HINGED STANDARD. RIGHT HAND OPTIONAL. (NO HEATERS REQ'D).
2. LIGHTS: HIGH OUTPUT/COOL WHITE STANDARD. SPX35 AVAIL. IN LIMITED BULB LENGTHS.
3. ELEC. CONNECTION: TOP MOUNTED 115V/230V, 4X4 SUPPLY BOX AS NEEDED.
4. REFG: STUBBED OUT TOP/REAR OF CASE.
5. COMPUTERIZED CASE CONTROLLERS: OPTIONAL.
6. EXPANSION VALVES: SPORLAN "Q" SERIES STANDARD UNLESS OTHERWISE SPECIFIED.
7. DEFROST CONTROL: RMT. CASE (N/A). OPTIONAL C.U. (PRESSURE CONTROL SWITCH).
8. THERMOSTATS & LIQUID LINE SOLENOID VALVES: OPTIONAL.
9. SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.

<b>borgen systems</b>			
SCALE: 1:16		DRAWN BY: D. HUNT	
DATE: 2-18-99		CHECKED BY:	
4 DOOR 4 BAY WINE			
DATE:	REV.	DIM: INCHES	DRAWING NUMBER
REVISION		TOL: ±1/4	P2922B