



CASE SPECIFICATIONS:

TOP AREA: 82.9 SQR FEET

REFRIGERATION

LOAD: 9,960 BTU/hr
 COIL: CTA 38-98.
 SUCTION TEMP: 20° F
 LIQUID LINE: 3/8IN ODS
 SUCTION LINE: 7/8IN ODS

ELECTRICAL 115V, 60HZ, 1PH.

EVAP. FANS: 3.3A
 MERCH. BALLASTS: 4.8A
 STORAGE BALLASTS: 0.8A
 TOTAL: 8.9A

WALKIN COOLER INFORMATION:

LIGHT SWITCH ADJACENT SERVICE DOOR.
 THERMOMETER ABOVE LIGHT SWITCH.
 VENT ABOVE THE SERVICE DOOR.

DISPLAY IN FORMATION:

BACK PANELS ON THE DIVIDING WALL ARE HINGED FOR REAR STOCKING.
 TEMPERED GLASS SHELVES ARE HIEGHT ADJUSTABLE.
 ENDS OF THE DISPLAY AREA ARE ENCLOSED WITH METAL DIVIDERS.

NOTES:

1. DOORS: LEFT HAND HINGED STANDARD. RIGHT HAND OPTIONAL. (NO HEATERS REQ'D).
2. LIGHTS: HIGH OUTPUT/COOL WHITE STANDARD. SPX35 AVAIL. IN LIMITED BULB LENGTHS.
3. ELEC. CONNECTION: TOP MOUNTED 115V/230V, 4X4 SUPPLY BOX AS NEEDED.
4. REFG: STUBBED OUT TOP/REAR OF CASE.
5. COMPUTERIZED CASE CONTROLERS: OPTIONAL.
6. EXPANSION VALVES: SPORLAN "Q" SERIES STANDARD UNLESS OTHERWISE SPECIFIED.
7. DEFROST CONTROL: RMT. CASE (N/A). OPTIONAL C.U. (PRESSURE CONTROL SWITCH).
8. THERMOSTATS & LIQUID LINE SOLENOID VALVES: OPTIONAL.
9. SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.

		borgen systems	
	SCALE: 1:24		DRAWN BY: D HUNT
	DATE: 11-19-99		CHECKED BY:
4 DOOR WOD WINE			
DATE:	REV.	DIM: INCHES	DRAWING NUMBER
REVISION		TOL: ±1/4	P3226B