

CASE SPECIFICATIONS:


REFRIGERATION
 LOAD: 6,900 BTU/hr
 SUCTION TEMP: 20° F
 LIQUID LINE: 3/8IN ODS
 SUCTION LINE: 5/8IN ODS

ELECTRICAL 115VAC, 60HZ, 1PH.
 EVAP. FANS: .26A
 LIGHT BALLAST: 1.88A
 CONDENSATE PUMP: 1.0A
 EVAP. PAN: 3.0A
 TOTAL: 6.14A
 MCA: 15.0A

ELECTRICAL 230VAC, 60HZ, 1PH.
 1 1/2HP COND. UNIT: 10.9A
 TOTAL: 7.7A
 MCA: 10.8A

NOTES:

1. OPTIONS NOT SHOWN ON DRAWING SHOULD BE LISTED IN WRITTEN PROPOSAL AND LISTED ON PURCHASE ORDER.
2. ELEC. CONNECTION: 115V/230V, 4x4 SUPPLY BOX AS NEEDED.
3. EXPANSION VALVES: SPORLAN "Q" SERIES STANDARD UNLESS OTHERWISE SPECIFIED.
4. DEFROST CONTROL: REMOTE CASES (N/A, DIGITAL CASE CONTROLERS AVAILABLE), OPTIONAL CONDENSING UNIT (DIGITAL CASE CONTROLLER).
5. THERMOSTATS & LIQUID LINE SOLENOID VALVES: OPTIONAL.
6. DRAIN: 1 INCH NATIONAL PIPE STRAIGHT THREAD.
7. SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.

		 börger systems	
		SCALE: 1:16	DRAWN BY: J MAUK
		DATE: 2-9-95	CHECKED BY:
8-23-04 DRH	4 DOOR		
12-15-03 DRH			
DATE	REV.	DIM: INCH	DRAWING NUMBER
REVISION	TOL:		P1875B