

**CASE SPECIFICATIONS:**


**REFRIGERATION**  
 LOAD: 7,475 BTU/hr  
 SUCTION TEMP: 20-26° F  
 LIQUID LINE: 3/8IN ODS  
 SUCTION LINE: 5/8IN ODS

**ELECTRICAL 115VAC, 60HZ, 1PH.**  
 EVAP. FANS: .26A  
 LIGHT BALLAST: 3.76A  
 TOTAL: 4.02A  
 MCA: 15.0A

**NOTES:**

1. OPTIONS NOT SHOWN ON DRAWING SHOULD BE LISTED IN WRITTEN PROPOSAL AND LISTED ON PURCHASE ORDER.
2. ELEC. CONNECTION: 115V/230V, 4x4 SUPPLY BOX AS NEEDED.
3. EXPANSION VALVES: SPORLAN "Q" SERIES STANDARD UNLESS OTHERWISE SPECIFIED.
4. DEFROST CONTROL: REMOTE CASES (N/A, DIGITAL CASE CONTROLLERS AVAILABLE), OPTIONAL CONDENSING UNIT (DIGITAL CASE CONTROLLER).
5. THERMOSTATS & LIQUID LINE SOLENOID VALVES: OPTIONAL.
6. DRAIN: 1 1/2 INCH PVC.
7. SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.



AUTHORIZATION (PRINT):		DATE:		 <b>börger systems</b>		SCALE: 1:24		DRAWN BY: J MAUK	
SIGNATURE:						DATE: 4-7-95		CHECKED BY:	
				7-22-08 DRH		6DR CORNER WRAP			
DATE		REV.		DIM: INCH		DRAWING NUMBER		P1924A	
REVISION		TOL:							