

CASE SPECIFICATIONS:


REFRIGERATION  
 LOAD: 3,450 BTU/hr  
 SUCTION TEMP: 20° F  
 LIQUID LINE: 3/8IN ODS  
 SUCTION LINE: 5/8IN ODS

ELECTRICAL 115VAC, 60HZ, 1PH.  
 EVAP. FANS: .13A  
 LIGHT BALLAST: .94A  
 CONDENSATE PUMP: 1.0A  
 EVAP. PAN: 3.0A  
 TOTAL: 5.07A

ELECTRICAL 230VAC, 60HZ, 1PH.  
 1/2HP COND. UNIT: 4.0A  
 TOTAL: 4.0A  
 MCA: 5.6A

NOTES:

1. OPTIONS NOT SHOWN ON DRAWING SHOULD BE LISTED IN WRITTEN PROPOSAL AND LISTED ON PURCHASE ORDER.
2. ELEC. CONNECTION: 115V/230V, 4x4 SUPPLY BOX AS NEEDED.
3. EXPANSION VALVES: SPORLAN "Q" SERIES STANDARD UNLESS OTHERWISE SPECIFIED.
4. DEFROST CONTROL: REMOTE CASES (N/A, DIGITAL CASE CONTROLLERS AVAILABLE), OPTIONAL CONDENSING UNIT (DIGITAL CASE CONTROLLER).
5. THERMOSTATS & LIQUID LINE SOLENOID VALVES: OPTIONAL.
6. DRAIN: 1 INCH NATIONAL PIPE STRAIGHT THREAD.
7. SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.

		 <b>börger systems</b>	
		SCALE: 1:12	DRAWN BY: S. HARRIS
		DATE: 9-22-95	CHECKED BY:
2-20-04	DRH	2 DOOR	
8-26-97	JMM		
DATE	REV.	DIM: INCH	DRAWING NUMBER
REVISION	TOL:		P2039B