



CASE SPECIFICATIONS:

REFRIGERATION

LOAD: 2,300 BTU/hr  
 SUCTION TEMP: 20° F  
 LIQUID LINE: 3/8IN ODS  
 SUCTION LINE: 5/8IN ODS

ELECTRICAL 115V, 60HZ, 1PH.

EVAP. FANS: 0.72A  
 LIGHT BALLASTS: 2.4A  
 CONDENSATE PUMP: 1.0A  
 EVAP. PAN: 3.0A  
 TOTAL: 7.12A

ELECTRICAL 230V, 60HZ, 1PH.

1/2HP COND. UNIT: 7.0A  
 TOTAL: 7.0A

NOTES:

1. DOORS: LEFT HAND HINGED STANDARD. RIGHT HAND OPTIONAL. (NO HEATERS REQ'D).
2. LIGHTS: HIGH OUTPUT/COOL WHITE STANDARD. SPX35 AVAIL. IN LIMITED BULB LENGTHS.
3. ELEC. CONNECTION: TOP MOUNTED 115V/230V, 4X4 SUPPLY BOX AS NEEDED.
4. REFG: R22 STANDARD UNLESS OTHERWISE SPEC. (STUBBED OUT TOP/REAR OF CASE).
5. COMPUTERIZED CASE CONTROLLERS: OPTIONAL.
6. EXPANSION VALVES: SPORLAN "Q" SERIES STANDARD UNLESS OTHERWISE SPECIFIED.
7. DEFROST CONTROL: RMT. CASE (N/A). OPTIONAL C.U. (PRESSURE CONTROL SWITCH).
8. THERMOSTATS & LIQUID LINE SOLENOID VALVES: OPTIONAL.
9. SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.

		<b>börger systems</b>	
		SCALE: 1:12	DRAWN BY: J. MAUK
		DATE: 7-15-96	CHECKED BY:
4-23-98	SEH	1 DOOR (2) GE2'S	
DATE:	REV.	DIM: INCHES	DRAWING NUMBER
REVISION		TOL: ±1/4	P2269B