

CASE SPECIFICATIONS:


REFRIGERATION  
 LOAD: 6,730 BTU/hr  
 SUCTION TEMP: 20° F  
 LIQUID LINE: 3/8IN ODS  
 SUCTION LINE: 5/8IN ODS

ELECTRICAL 115VAC,  
 60HZ, 1PH.  
 EVAP. FANS: .39A  
 LIGHT BALLAST: 1.88A  
 CONDENSATE PUMP: 1.0A  
 TOTAL: 3.27A  
 MCA: 15.0A

ELECTRICAL 230VAC,  
 60HZ, 1PH.  
 EVAP. PAN: 7.2A  
 1HP COND. UNIT: 7.7A  
 TOTAL: 14.9A  
 MCA: 18.0A

NOTES:

1. OPTIONS NOT SHOWN ON DRAWING SHOULD BE LISTED IN WRITTEN PROPOSAL AND LISTED ON PURCHASE ORDER.
2. ELEC. CONNECTION: 115V/230V, 4x4 SUPPLY BOX AS NEEDED.
3. EXPANSION VALVES: SPORLAN "Q" SERIES STANDARD UNLESS OTHERWISE SPECIFIED.
4. DEFROST CONTROL: REMOTE CASES (N/A, DIGITAL CASE CONTROLLERS AVAILABLE), OPTIONAL CONDENSING UNIT (DIGITAL CASE CONTROLLER).
5. THERMOSTATS & LIQUID LINE SOLENOID VALVES: OPTIONAL.
6. DRAIN: 1 INCH NATIONAL PIPE STRAIGHT THREAD.
7. SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.

		 börger systems	
		SCALE: 1:16	DRAWN BY: D. HUNT
		DATE: 5-4-99	CHECKED BY:
1DR 4FT DF OPEN RIGHT			
DATE	REV	DIM: INCH	DRAWING NUMBER
REVISION		TOL:	P3004B