



CASE SPECIFICATIONS:

REFRIGERATION

LOAD: 3,036 BTU/hr
 SUCTION TEMP: 30° F
 LIQUID LINE: 3/8IN ODS
 SUCTION LINE: 5/8IN ODS

ELECTRICAL 115V, 60HZ, 1PH.

EVAP. FANS: 0.72A
 LIGHT BALLASTS: 4.8A
 CONDENSATE PUMP: 1.0A
 EVAP. PAN: 3.0A
 1/3HP COND. UNIT: 10.0A
 TOTAL: 19.52A

NOTES:

1. DOORS: LEFT HAND HINGED STANDARD. RIGHT HAND OPTIONAL. (NO HEATERS REQ'D).
2. LIGHTS: HIGH OUTPUT/COOL WHITE STANDARD. SPX35 AVAIL. IN LIMITED BULB LENGTHS.
3. ELEC. CONNECTION: TOP MOUNTED 115V/230V, 4X4 SUPPLY BOX AS NEEDED.
4. REFG: STUBBED OUT TOP/REAR OF CASE.
5. COMPUTERIZED CASE CONTROLLERS: OPTIONAL.
6. EXPANSION VALVES: SPORLAN "Q" SERIES STANDARD UNLESS OTHERWISE SPECIFIED.
7. DEFROST CONTROL: RMT. CASE (N/A). OPTIONAL C.U. (PRESSURE CONTROL SWITCH).
8. THERMOSTATS & LIQUID LINE SOLENOID VALVES: OPTIONAL.
9. SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.

börger systems			
SCALE:	1:12	DRAWN BY:	D HUNT
DATE:	6-3-99	CHECKED BY:	
2 DOOR (2) GE2 WINE			
DATE:	REV.	DIM: INCHES	DRAWING NUMBER
REVISION		TOL: ±1/4	P3040B