

CASE SPECIFICATIONS:

REFRIGERATION:


LOAD: 14,175 BTU/hr

SUCTION TEMP: 20°F  
 SUCTION LINE: 5/8IN ODS  
 LIQUID LINE: 3/8IN ODS

ELECTRICAL 115V, 60HZ, 1PH  
 EVAP. FANS: 2.16A  
 LIGHT BALLASTS: 2.3A  
 LIGHT TRANSFORMERS: 2.6A  
 TOTAL: 7.06A  
 MCA: 15.0A

NOTES:

1. OPTIONS NOT SHOWN ON DRAWING SHOULD BE LISTED IN WRITTEN PROPOSAL AND LISTED ON PURCHASE ORDER.
2. ELEC. CONNECTION: 115V/230V, 4x4 SUPPLY BOX AS NEEDED.
3. EXPANSION VALVES: SPORLAN "Q" SERIES STANDARD UNLESS OTHERWISE SPECIFIED.
4. DEFROST CONTROL: REMOTE CASES (N/A, DIGITAL CASE CONTROLLERS AVAILABLE), OPTIONAL CONDENSING UNIT (DIGITAL CASE CONTROLLER).
5. THERMOSTATS & LIQUID LINE SOLENOID VALVES: OPTIONAL.
6. DRAIN: 1 1/2 INCH PVC.
7. SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.

AUTHORIZATION (PRINT):	DATE:	 <b>börger systems</b>		DRAWN BY: D HUNT
SIGNATURE:				SCALE: 1:32
		DATE: 7-21-02	5DR, 10FT HUTCH	
6-28-05	DRH			DRAWING NUMBER
DATE	REV.	DIM:	INCH	P3502A
REVISION	TOL:			