

CASE SPECIFICATIONS:


REFRIGERATION:  
LOAD: 11,300 BTU/hr

SUCTION TEMP: 20°F  
SUCTION LINE: 5/8IN ODS  
LIQUID LINE: 3/8IN ODS

ELECTRICAL 115V, 60HZ, 1PH  
EVAP. FANS: 1.66A  
LIGHT BALLASTS: 1.48A  
LIGHT TRANSFORMERS: 2.6A  
TOTAL: 5.74A  
MCA: 15.0A

NOTES:

1. OPTIONS NOT SHOWN ON DRAWING SHOULD BE LISTED IN WRITTEN PROPOSAL AND LISTED ON PURCHASE ORDER.
2. ELEC. CONNECTION: 115V/230V, 4x4 SUPPLY BOX AS NEEDED.
3. EXPANSION VALVES: SPORLAN "Q" SERIES STANDARD UNLESS OTHERWISE SPECIFIED.
4. DEFROST CONTROL: REMOTE CASES (N/A, DIGITAL CASE CONTROLLERS AVAILABLE), OPTIONAL CONDENSING UNIT (DIGITAL CASE CONTROLLER).
5. THERMOSTATS & LIQUID LINE SOLENOID VALVES: OPTIONAL.
6. DRAIN: 1 1/2 INCH PVC.
7. SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.

AUTHORIZATION (PRINT):	DATE:			 <b>börger systems</b>	
SIGNATURE:		SCALE: 1:32	DATE: 7-21-00		
		9-14-07 DRH	4DR, 8FT HUTCH		
		5-24-05 DRH			
		DATE REV. DIM: INCH			DRAWING NUMBER
		REVISION TOL:			P3503A