

CASE SPECIFICATIONS:


REFRIGERATION
 DOORED: 2,875 BTU/hr
 OPEN: 5,580 BTU/hr
 TOTAL: 8,455 BTU/hr
 SUCTION TEMP: 20° F
 LIQUID LINE: 3/8IN ODS
 SUCTION LINE: 5/8IN ODS

ELECTRICAL 115VAC, 60HZ, 1PH.
 EVAP. FANS: .39A
 LIGHT BALLAST: 1.48A
 COND. PUMP: 1.0A
 TOTAL: 2.87A
 MCA: 15.0A

ELECTRICAL 208-230VAC, 60HZ, 1PH.
 COND. PAN: 7.2A
 1 1/2HP COND. UNIT: 10.9A
 TOTAL: 18.1A
 MCA: 23.7A

NOTES:

1. OPTIONS NOT SHOWN ON DRAWING SHOULD BE LISTED IN WRITTEN PROPOSAL AND LISTED ON PURCHASE ORDER.
2. ELEC. CONNECTION: 115V/230V, 4x4 SUPPLY BOX AS NEEDED.
3. EXPANSION VALVES: SPORLAN "Q" SERIES STANDARD UNLESS OTHERWISE SPECIFIED.
4. DEFROST CONTROL: REMOTE CASES (N/A, DIGITAL CASE CONTROLLERS AVAILABLE), OPTIONAL CONDENSING UNIT (DIGITAL CASE CONTROLLER).
5. THERMOSTATS & LIQUID LINE SOLENOID VALVES: OPTIONAL.
6. DRAIN: 1 1/2 INCH PVC.
7. SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.

AUTHORIZATION (PRINT):	DATE:	 börger systems		DRAWN BY: D HUNT
SIGNATURE:				SCALE: 1:24
		DATE: 4-9-01	2DR 4FT DF COMBO	
		4-14-05 DRH	DRAWING NUMBER	
DATE	REV.	DIM:	INCH	P3724A
REVISION	TOL:			