

CASE SPECIFICATIONS:

REFRIGERATION
 LOAD: 19,800 BTU/hr
 SUCTION TEMP: 20° F
 LIQUID LINE: 3/8IN ODS
 SUCTION LINE: 5/8IN ODS


ELECTRICAL 115VAC, 60HZ, 1PH.
 EVAP. FANS: .78A
 LIGHT BALLAST: 1.86A
 FRESH WATER SYSTEM: 5.0A
 TOTAL: 7.64A
 MCA: 15.0A

ELECTRICAL 208/230VAC, 60HZ, 1PH.
 (2) 1 1/4 HP COND. UNIT: 19.2A
 TOTAL: 19.2A
 MCA: 29.8A

NOTES:

1. OPTIONS NOT SHOWN ON DRAWING SHOULD BE LISTED IN WRITTEN PROPOSAL AND LISTED ON PURCHASE ORDER.
2. ELEC. CONNECTION: 115V/230V, 4x4 SUPPLY BOX AS NEEDED.
3. EXPANSION VALVES: SPORLAN "Q" SERIES STANDARD UNLESS OTHERWISE SPECIFIED.
4. DEFROST CONTROL: REMOTE CASES (N/A, DIGITAL CASE CONTROLLERS AVAILABLE), OPTIONAL CONDENSING UNIT (DIGITAL CASE CONTROLLER).
5. THERMOSTATS & LIQUID LINE SOLENOID VALVES: OPTIONAL.
6. DRAIN: 1 INCH NATIONAL PIPE STRAIGHT THREAD.
7. SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.

FLOOR DRAIN MUST BE PROVIDED FOR THIS CASE

		 börger systems	
		SCALE: 1:16	DRAWN BY: A. BESIC
		DATE: 10-2-03	CHECKED BY:
5-25-07	DRH	12FT OPEN FWE	
DATE	REV.	DIM: INCH	DRAWING NUMBER
REVISION	TOL:		P4243B