

**CASE SPECIFICATIONS:**


**REFRIGERATION**  
 LOAD: 5,500 BTU/hr  
 SUCTION TEMP: 30° F  
 LIQUID LINE: 3/8IN ODS  
 SUCTION LINE: 5/8IN ODS

**ELECTRICAL 115VAC, 60HZ, 1PH.**  
 EVAP. FANS: .13A  
 LIGHT BALLAST: 1.88A  
 CONDENSATE PUMP: 1.0A  
 TOTAL: 3.01A  
 MCA: 15.0A

**ELECTRICAL 230VAC, 60HZ, 1PH.**  
 EVAP. PAN: 6.5A  
 3/4HP COND. UNIT: 6.1A  
 TOTAL: 12.6A  
 MCA: 15.3A

**NOTES:**

1. OPTIONS NOT SHOWN ON DRAWING SHOULD BE LISTED IN WRITTEN PROPOSAL AND LISTED ON PURCHASE ORDER.
2. ELEC. CONNECTION: 115V/230V, 4x4 SUPPLY BOX AS NEEDED.
3. EXPANSION VALVES: SPORLAN "Q" SERIES STANDARD UNLESS OTHERWISE SPECIFIED.
4. DEFROST CONTROL: REMOTE CASES (N/A, DIGITAL CASE CONTROLLERS AVAILABLE), OPTIONAL CONDENSING UNIT (DIGITAL CASE CONTROLLER).
5. THERMOSTATS & LIQUID LINE SOLENOID VALVES: OPTIONAL.
6. DRAIN: 1 1/2 INCH PVC.
7. SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.

AUTHORIZATION (PRINT):	DATE:	 <b>börger systems</b>		DRAWN BY: D HUNT
SIGNATURE:				SCALE: 1:24
		DATE: 12-15-03	4FT HC WINE	
11-19-04	DRH			DRAWING NUMBER
DATE	REV.	DIM:	INCH	P4313A
REVISION	TOL:			