


**CASE SPECIFICATIONS:**

REFRIGERATION GLYCOL  
 LOAD: 3,450 BTU/hr  
 GLYCOL TEMP: 20F  
 %G CON: 35  
 GPM: 0.65  
 PRES. DROP: .60  
 LINE: 7/8IN ODS

ELECTRICAL 115VAC, 60HZ, 1PH.  
 EVAP. FANS: .26A  
 LIGHT BALLAST: .1.48A  
 TOTAL: 1.74A

**NOTES:**

1. OPTIONS NOT SHOWN ON DRAWING SHOULD BE LISTED IN WRITTEN PROPOSAL AND LISTED ON PURCHASE ORDER.
2. ELEC. CONNECTION: 115V/230V, 4x4 SUPPLY BOX AS NEEDED.
3. EXPANSION VALVES: SPORLAN "Q" SERIES STANDARD UNLESS OTHERWISE SPECIFIED.
4. DEFROST CONTROL: REMOTE CASES (N/A, DIGITAL CASE CONTROLLERS AVAILABLE), OPTIONAL CONDENSING UNIT (DIGITAL CASE CONTROLLER).
5. THERMOSTATS & LIQUID LINE SOLENOID VALVES: OPTIONAL.
6. DRAIN: 1 INCH NATIONAL PIPE STRAIGHT THREAD.
7. SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.

		 <b>börger systems</b>	
SCALE:	1:16	DRAWN BY: D HUNT	
DATE:	2-12-04	CHECKED BY:	
2DR INSIDE WRAP			
DATE	REV.	DIM: INCH	DRAWING NUMBER
REVISION	TOL:		P4365B