

CASE SPECIFICATIONS:

REFRIGERATION  
 LOAD: 6,600 BTU/hr  
 COIL TEMP: 22° F  
 LIQUID STUB: 3/8IN ODS  
 SUCTION STUB: 1/2IN ODS


ELECTRICAL 115VAC, 60HZ, 1PH.  
 EVAP. FANS: .26A  
 COND. PUMP: 1.0A  
 TOTAL: 1.26A  
 MCA: 15.0A

ELECTRICAL 115VAC, 60HZ, 1PH.  
 EVAP. PAN: 7.2A  
 1HP COND. UNIT: 7.7A  
 TOTAL: 14.9A  
 MCA: 18.0A

OPTIONAL LIGHTS  
 ELECTRICAL 115VAC, 60HZ, 1PH.  
 LIGHTS: 1.48A  
 TOTAL: 1.48A  
 MCA: 15.0A

NOTES:

1. OPTIONS NOT SHOWN ON DRAWING SHOULD BE LISTED IN WRITTEN PROPOSAL AND LISTED ON PURCHASE ORDER.
2. ELEC. CONNECTION: 115V/230V, 4x4 SUPPLY BOX AS NEEDED.
3. EXPANSION VALVES: SPORLAN "Q" SERIES STANDARD UNLESS OTHERWISE SPECIFIED.
4. DEFROST CONTROL: REMOTE CASES (N/A, DIGITAL CASE CONTROLLERS AVAILABLE), OPTIONAL CONDENSING UNIT (DIGITAL CASE CONTROLLER).
5. THERMOSTATS & LIQUID LINE SOLENOID VALVES: OPTIONAL.
6. DRAIN: 1 1/2 INCH PVC.
7. SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.

AUTHORIZATION (PRINT):	DATE:			 <b>börgeren systems</b>		DRAWN BY: D HUNT
SIGNATURE:		SCALE: 1:32	DATE: 3-24-04			CHECKED BY:
		10-3-08 DRH		6FT LPM FIELD OF FLOWERS		
		10-13-04 DRH				
		DATE	REV.	DIM:	INCH	DRAWING NUMBER P4406
		REVISION	TOL:			