

CASE SPECIFICATIONS:


REFRIGERATION
 LOAD: 17,500 BTU/hr
 SUCTION TEMP: 20°
 LIQUID LINE: 3/8IN ODS
 SUCTION LINE: 5/8IN ODS

ELECTRICAL 115VAC, 60HZ, 1PH.
 EVAP. FANS: .78A
 LIGHT BALLAST: 2.96A
 (1) CONDENSATE PUMP: 2.0A
 TOTAL: 5.74A
 MCA: 15.0A

ELECTRICAL 230VAC, 60HZ, 1PH.
 (2) EVAP. PAN: 14.4A
 (2) 1 1/2HP COND. UNIT: 21.8A
 TOTAL: 36.2A
 MCA: 48.0A

NOTES:

1. OPTIONS NOT SHOWN ON DRAWING SHOULD BE LISTED IN WRITTEN PROPOSAL AND LISTED ON PURCHASE ORDER.
2. ELEC. CONNECTION: 115V/230V, 4x4 SUPPLY BOX AS NEEDED.
3. EXPANSION VALVES: SPORLAN "Q" SERIES STANDARD UNLESS OTHERWISE SPECIFIED.
4. DEFROST CONTROL: REMOTE CASES (N/A, DIGITAL CASE CONTROLLERS AVAILABLE), OPTIONAL CONDENSING UNIT (DIGITAL CASE CONTROLLER).
5. THERMOSTATS & LIQUID LINE SOLENOID VALVES: OPTIONAL.
6. DRAIN: 1 INCH NATIONAL PIPE STRAIGHT THREAD.
7. SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.

		 börger systems	
		SCALE: 1:12	DRAWN BY: D HUNT
		DATE: 5-10-04	CHECKED BY:
12FT DF			
DATE	REV.	DIM: INCH	DRAWING NUMBER
REVISION		TOL:	P4444B