


**CASE SPECIFICATIONS:**

**REFRIGERATION**  
 LOAD: 4,100 BTU/hr  
 SUCTION TEMP: 30° F  
 LIQUID LINE: 3/8IN ODS  
 SUCTION LINE: 5/8IN ODS

**ELECTRICAL** 115VAC, 60HZ, 1PH.  
 EVAP. FANS: .26A  
 LIGHT BALLAST: 1.48A  
 CONDENSATE PUMP: 1.0A  
 EVAP. PAN: 3.0A  
 1/2HP COND. UNIT: 9.2A  
 TOTAL: 14.94A  
 MCA: 18.1A

**NOTES:**

1. OPTIONS NOT SHOWN ON DRAWING SHOULD BE LISTED IN WRITTEN PROPOSAL AND LISTED ON PURCHASE ORDER.
2. ELEC. CONNECTION: 115V/230V, 4x4 SUPPLY BOX AS NEEDED.
3. EXPANSION VALVES: SPORLAN "Q" SERIES STANDARD UNLESS OTHERWISE SPECIFIED.
4. DEFROST CONTROL: REMOTE CASES (N/A, DIGITAL CASE CONTROLLERS AVAILABLE), OPTIONAL CONDENSING UNIT (DIGITAL CASE CONTROLLER).
5. THERMOSTATS & LIQUID LINE SOLENOID VALVES: OPTIONAL.
6. DRAIN: 1 INCH NATIONAL PIPE STRAIGHT THREAD.
7. SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.

				<b>börger systems</b>	
		SCALE: 1:16			DRAWN BY: D HUNT
		DATE: 9-24-04			CHECKED BY:
3DR 2BAY WINE					
DATE	REV.	DIM:	INCH	DRAWING NUMBER	
REVISION		TOL:		P4531B	