

CASE SPECIFICATIONS:


REFRIGERATION
 LOAD: 14,100 BTU/hr
 SUCTION TEMP: 30° F
 LIQUID LINE: 3/8IN ODS
 SUCTION LINE: 5/8IN ODS

ELECTRICAL 115VAC, 60HZ, 1PH.
 EVAP. FANS: .52A
 LIGHT BALLAST: 5.92A
 TOTAL: 6.44A

BOTTLES: 728

NOTES:

1. OPTIONS NOT SHOWN ON DRAWING SHOULD BE LISTED IN WRITTEN PROPOSAL AND LISTED ON PURCHASE ORDER.
2. ELEC. CONNECTION: 115V/230V, 4x4 SUPPLY BOX AS NEEDED.
3. EXPANSION VALVES: SPORLAN "Q" SERIES STANDARD UNLESS OTHERWISE SPECIFIED.
4. DEFROST CONTROL: REMOTE CASES (N/A, DIGITAL CASE CONTROLLERS AVAILABLE), OPTIONAL CONDENSING UNIT (DIGITAL CASE CONTROLLER).
5. THERMOSTATS & LIQUID LINE SOLENOID VALVES: OPTIONAL.
6. DRAIN: 1 1/2 INCH PVC.
7. SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.

AUTHORIZATION (PRINT):	DATE:			 börgeren systems		DRAWN BY: D HUNT
SIGNATURE:		SCALE: 1:24	DATE: 3-25-04			CHECKED BY:
		2-13-08 DRH	8FT HC WINE			
		11-19-04 DRH				
		DATE	REV.	DIM:	INCH	DRAWING NUMBER
		REVISION	TOL:			P4576A