



CASE SPECIFICATIONS:

REFRIGERATION
 LOAD: 7,650 BTU/hr
 SUCTION TEMP: 20° F
 LIQUID LINE: 3/8IN ODS
 SUCTION LINE: 5/8IN ODS
 ELECTRICAL 115VAC, 60HZ, 1PH.
 EVAP. FANS: 2.34A
 LIGHT BALLAST: 1.5A
 TOTAL: 3.84A
 MCA: 15.0A

NOTES:

1. OPTIONS NOT SHOWN ON DRAWING SHOULD BE LISTED IN WRITTEN PROPOSAL AND LISTED ON PURCHASE ORDER.
2. ELEC. CONNECTION: 115V/230V, 4x4 SUPPLY BOX AS NEEDED.
3. EXPANSION VALVES: SPORLAN "Q" SERIES STANDARD UNLESS OTHERWISE SPECIFIED.
4. DEFROST CONTROL: REMOTE CASES (N/A, DIGITAL CASE CONTROLLERS AVAILABLE), OPTIONAL CONDENSING UNIT (DIGITAL CASE CONTROLLER).
5. THERMOSTATS & LIQUID LINE SOLENOID VALVES: OPTIONAL.
6. DRAIN: 1 1/2 INCH PVC.
7. SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.

börger systems

AUTHORIZATION (PRINT):		DATE:	
SIGNATURE:		SCALE: 1:24	
		DATE: 12-14-05	
		8' SELF SERV. MERCH. DRAWING NUMBER BG8SSM P4754A	
DATE	REV	DATE	REV
REVISION	TOL.	DATE	REV