



CASE SPECIFICATIONS:

REFRIGERATION
 LOAD: 5,750 BTU/hr
 SUCTION TEMP: 20° F
 LIQUID LINE: 3/8IN ODS
 SUCTION LINE: 5/8IN ODS
 ELECTRICAL 115VAC, 60HZ, 1PH.
 EVAP. FANS: 1.56A
 LIGHT BALLAST: 1.0A
 TOTAL: 2.56A
 MCA: 15.0A

NOTES:

1. OPTIONS NOT SHOWN ON DRAWING SHOULD BE LISTED IN WRITTEN PROPOSAL AND LISTED ON PURCHASE ORDER.
2. ELEC. CONNECTION: 115V/230V, 4x4 SUPPLY BOX AS NEEDED.
3. EXPANSION VALVES: SPORLAN "Q" SERIES STANDARD UNLESS OTHERWISE SPECIFIED.
4. DEFROST CONTROL: REMOTE CASES (N/A, DIGITAL CASE CONTROLLER).
5. THERMOSTATS & LIQUID LINE SOLENOID VALVES: OPTIONAL.
6. DRAIN: 1 1/2 INCH PVC.
7. SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.

börger systems



SCALE: 1:24
 DATE: 12-20-05
 DRAWN BY: D HUNT
 CHECKED BY:

6' SELF SERV. MERCH. BG6SSM
 DRAWING NUMBER: P4765A

DATE	REV	DRW	INCH	TOL.
2-7-06	DRH			

AUTHORIZATION (PRINT):

DATE:

SIGNATURE: