

CASE SPECIFICATIONS:


REFRIGERATION
 LOAD: 7,200 BTU/hr
 SUCTION TEMP: -20° F
 LIQUID LINE: 3/8IN ODS
 SUCTION LINE: 5/8IN ODS

ELECTRICAL 115VAC, 60HZ, 1PH.
 LIGHT BALLAST: 7.5A
 DOOR HEATER: 9.66A
 TOTAL: 17.16A

ELECTRICAL 208VAC, 60HZ, 1PH.
 DEFROST HEATER: 10.5A
 EVAP. FANS: 6.6A
 TOTAL: 17.1

NOTES:

1. OPTIONS NOT SHOWN ON DRAWING SHOULD BE LISTED IN WRITTEN PROPOSAL AND LISTED ON PURCHASE ORDER.
2. ELEC. CONNECTION: 115V/230V, 4x4 SUPPLY BOX AS NEEDED.
3. EXPANSION VALVES: SPORLAN "Q" SERIES STANDARD UNLESS OTHERWISE SPECIFIED.
4. DEFROST CONTROL: REMOTE CASES (N/A, DIGITAL CASE CONTROLLERS AVAILABLE), OPTIONAL CONDENSING UNIT (DIGITAL CASE CONTROLLER).
5. THERMOSTATS & LIQUID LINE SOLENOID VALVES: OPTIONAL.
6. DRAIN: 1 1/2 INCH PVC.
7. SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.

AUTHORIZATION (PRINT):	DATE:	 börger systems		SCALE: 1:24	DRAWN BY: D THOMAS
SIGNATURE:				DATE: 2-20-06	CHECKED BY:
		8FT FREEZER BG8F			
DATE	REV.	QTY	INCH	DRAWING NUMBER	
REVISION		TOL:		P4809A	