

BOTTLES PER DOOR: 224
TOTAL FOR CASE: 896

CASE SPECIFICATIONS:


REFRIGERATION:
LOAD: 5,060 BTU/hr
SUCTION TEMP: 30°F
SUCTION LINE: 5/8IN ODS
LIQUID LINE: 3/8IN ODS

ELECTRICAL 115V, 60HZ, 1PH
EVAP. FANS: 0.13A
LIGHT BALLASTS: 2.40A
CONDENSATE PUMP: 1.0A
CONDENSATE PAN: 3.0A
TOTAL: 6.53A
MCA: 15.0A

OPTIONAL ELECTRICAL 208V, 60HZ, 1PH
3/4 HP COND. UNIT: 6.1A
TOTAL: 6.1A
MCA: 8.8A

NOTES:

1. OPTIONS NOT SHOWN ON DRAWING SHOULD BE LISTED IN WRITTEN PROPOSAL AND LISTED ON PURCHASE ORDER.
2. ELEC. CONNECTION: 115V/230V, 4x4 SUPPLY BOX AS NEEDED.
3. EXPANSION VALVES: SPORLAN "Q" SERIES STANDARD UNLESS OTHERWISE SPECIFIED.
4. DEFROST CONTROL: REMOTE CASES (N/A, DIGITAL CASE CONTROLLERS AVAILABLE), OPTIONAL CONDENSING UNIT (DIGITAL CASE CONTROLLER).
5. THERMOSTATS & LIQUID LINE SOLENOID VALVES: OPTIONAL.
6. DRAIN: 1 INCH NATIONAL PIPE STRAIGHT THREAD.
7. SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.

		 börger systems	
		SCALE: 1:12	DRAWN BY: D. HUNT
		DATE: 3-2-06	CHECKED BY:
4 DOOR WINE			
DATE	REV.	DIM: INCH	DRAWING NUMBER
REVISION	TOL:		P4819B