



Note:
Unless specified this case will have the full 6' of refrigerated rear storage.

1. OPTIONS NOT SHOWN ON DRAWING SHOULD BE LISTED IN WRITTEN PROPOSAL AND LISTED ON PURCHASE ORDER.
2. ELEC. CONNECTION: 115V/230V, 4x4 SUPPLY BOX AS NEEDED.
3. EXPANSION VALVES: SPORLAN "Q" SERIES STANDARD UNLESS OTHERWISE SPECIFIED.
4. DEFROST CONTROL: REMOTE CASES (N/A, DIGITAL CASE CONTROLLERS AVAILABLE), OPTIONAL CONDENSING UNIT (DIGITAL CASE CONTROLLER).
5. THERMOSTATS & LIQUID LINE SOLENOID VALVES: OPTIONAL.
6. DRAIN: 1 1/2 INCH PVC.
7. SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.

DLI100 6' REMOTE GOURMET SANDWICH SPECIFICATIONS:

REFRIGERATION
LOAD: 3000 BTU/hr
SUCTION TEMP: 20° F
LIQUID LINE: 3/8IN ODS
SUCTION LINE: 5/8IN ODS

ELECTRICAL 115VAC, 60HZ, 1PH.
EVAP. FANS: 1.04A
TOTAL: 2.04A

börger systems

SCALE: 1:x

DRAWN BY: DWT

DATE: MM-DD-02

CHECKED BY:

DLI100-BG6GSM

		börger systems	
		SCALE: 1:x	DRAWN BY: DWT
		DATE: MM-DD-02	CHECKED BY:
		DLI100-BG6GSM	
DATE	REV.	DIM: INCH	DRAWING NUMBER
REVISION		TOL: ±1/32	P4830A