



DLI100 8' REMOTE GOURMET SANDWICH
SPECIFICATIONS:

REFRIGERATION
LOAD: 2000 BTU/hr
SUCTION TEMP: 20° F
LIQUID LINE: 3/8IN ODS
SUCTION LINE: 5/8IN ODS

ELECTRICAL 115VAC, 60HZ, 1PH.
EVAP. FANS: 1.04A
TOTAL: 1.04A

1. OPTIONS NOT SHOWN ON DRAWING SHOULD BE LISTED IN WRITTEN PROPOSAL AND LISTED ON PURCHASE ORDER.
2. ELEC. CONNECTION: 115V/230V, 4x4 SUPPLY BOX AS NEEDED.
3. EXPANSION VALVES: SPORLAN "Q" SERIES STANDARD UNLESS OTHERWISE SPECIFIED.
4. DEFROST CONTROL: REMOTE CASES (N/A, DIGITAL CASE CONTROLLERS AVAILABLE), OPTIONAL CONDENSING UNIT (DIGITAL CASE CONTROLLER).
5. THERMOSTATS & LIQUID LINE SOLENOID VALVES: OPTIONAL.
6. DRAIN: 1 1/2 INCH PVC.
7. SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.

Borgen Systems
1901 Bell Avenue, Suite 2
Des Moines, IA 50315
www.borgensystems.com

DATE: 5/16/2006

DRAWN BY: dont

8 Ft Gourmet Sandwich Rear Drawers

DIM: INCH

DRAWING NUMBER:

TOL: +/- 1/32

BG-8GSD

P4840A



Commercial Refrigerator
Less Condensing Unit