



CASE SPECIFICATIONS:

REFRIGERATION
 LOAD: 10,300 BTU/hr
 SUCTION TEMP: 20° F
 LIQUID LINE: 3/8IN ODS
 SUCTION LINE: 7/8IN ODS

ELECTRICAL 208/230V, 60HZ, 1PH.
 EVAP FANS: .26A
 EVAP. PAN: 14.4A
 1 1/2HP COND. UNIT: 10.9A
 TOTAL: 25.56A
 MCA: 31.0A

DISCHARGE AIR TEMPERATURES:
 CUT-IN 38°F
 CUT-OUT 35°F

DEFROST:
 6 TIMES PER DAY
 DURATION 20 MINUTES

TD DISCHARGE TO PRODUCT:
 3-8°F

NOTES:

1. OPTIONS NOT SHOWN ON DRAWING SHOULD BE LISTED IN WRITTEN PROPOSAL AND LISTED ON PURCHASE ORDER.
2. ELEC. CONNECTION: 115V/230V, 4x4 SUPPLY BOX AS NEEDED.
3. EXPANSION VALVES: SPORLAN "Q" SERIES STANDARD UNLESS OTHERWISE SPECIFIED.
4. DEFROST CONTROL: REMOTE CASES (N/A, DIGITAL CASE CONTROLLERS AVAILABLE), OPTIONAL CONDENSING UNIT (DIGITAL CASE CONTROLLER).
5. THERMOSTATS & LIQUID LINE SOLENOID VALVES: OPTIONAL.
6. DRAIN: 1 1/2 INCH PVC.
7. SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.

AUTHORIZATION (PRINT):	DATE:						
SIGNATURE:		7-10-07 DRH	SCALE: 1:24	7-2-07 DRH	DATE: 5-21-07		DRAWN BY: D HUNT
		6-27-07 DRH	6FT FLOWER MOUND				CHECKED BY:
		5-22-07 DRH	DATE	REV.	DIM:	INCH	P5122A
			REVISION	TOL:			