

CASE SPECIFICATIONS:


REFRIGERATION
 LOAD: 5,300 BTU/hr
 SUCTION TEMP: 20° F
 LIQUID LINE: 3/8IN ODS
 SUCTION LINE: 5/8IN ODS

ELECTRICAL 115VAC, 60HZ, 1PH.
 EVAP. FANS: .65A
 LIGHT BALLAST: 2.82A
 TOTAL: 3.47A
 MCA: 15.0A

ELECTRICAL 230VAC, 60HZ, 1PH.
 (4) WELLS 11QT HEATERS: 3.0A
 TOTAL: 12.0A
 MCA: 15.0A

NOTES:

1. OPTIONS NOT SHOWN ON DRAWING SHOULD BE LISTED IN WRITTEN PROPOSAL AND LISTED ON PURCHASE ORDER.
2. ELEC. CONNECTION: 115V/230V, 4x4 SUPPLY BOX AS NEEDED.
3. EXPANSION VALVES: SPORLAN "Q" SERIES STANDARD UNLESS OTHERWISE SPECIFIED.
4. DEFROST CONTROL: REMOTE CASES (N/A, DIGITAL CASE CONTROLLERS AVAILABLE), OPTIONAL CONDENSING UNIT (DIGITAL CASE CONTROLLER).
5. THERMOSTATS & LIQUID LINE SOLENOID VALVES: OPTIONAL.
6. DRAIN: 1 1/2 INCH PVC.
7. SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.

AUTHORIZATION (PRINT):		DATE:		 börger systems		SCALE: 1:32		DRAWN BY: D HUNT	
SIGNATURE:						DATE: 1-28-08		CHECKED BY:	
				13FT SALAD BAR					
DATE		REV		DIM: INCH		DRAWING NUMBER		P5314A	
REVISION		TOL:							