

**8FT CASE SPECIFICATIONS:**

REFRIGERATION  
 LOAD: 10,800 BTU/hr  
 SUCTION TEMP: 20° F  
 LIQUID LINE: 3/8IN ODS  
 SUCTION LINE: 5/8IN ODS

ELECTRICAL 115VAC, 60HZ, 1PH.  
 EVAP. FANS: .52A  
 LIGHT BALLAST: 1.88A  
 FRESH WATER SYSTEM: 5.0A  
 TOTAL: 7.4A  
 MCA: 15.0A

**4FT CASE SPECIFICATIONS:**


REFRIGERATION  
 LOAD: 5,580 BTU/hr  
 SUCTION TEMP: 20°  
 LIQUID LINE: 3/8IN ODS  
 SUCTION LINE: 5/8IN ODS

ELECTRICAL 115VAC, 60HZ, 1PH.  
 EVAP. FANS: .26A  
 LIGHT BALLAST: 2.4A  
 TOTAL: 2.66A

**NOTES:**

1. OPTIONS NOT SHOWN ON DRAWING SHOULD BE LISTED IN WRITTEN PROPOSAL AND LISTED ON PURCHASE ORDER.
2. ELEC. CONNECTION: 115V/230V, 4x4 SUPPLY BOX AS NEEDED.
3. EXPANSION VALVES: SPORLAN "Q" SERIES STANDARD UNLESS OTHERWISE SPECIFIED.
4. DEFROST CONTROL: REMOTE CASES (N/A, DIGITAL CASE CONTROLLERS AVAILABLE), OPTIONAL CONDENSING UNIT (DIGITAL CASE CONTROLLER).
5. THERMOSTATS & LIQUID LINE SOLENOID VALVES: OPTIONAL.
6. DRAIN: 1 1/2 INCH PVC.
7. SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.

FLOOR DRAIN MUST BE PROVIDED FOR THIS CASE

AUTHORIZATION (PRINT):		DATE:		 <b>börger systems</b>		SCALE: 1:32	DRAWN BY: D HUNT
SIGNATURE:						DATE: 4-3-08	CHECKED BY:
				8FT FWE & 4FT DF			
DATE	REV	DN:	INCH			DRAWING NUMBER	
REVISION		TOL:				P5384A	