

CASE SPECIFICATIONS:


REFRIGERATION
 LOAD: 13,200 BTU/hr
 COIL TEMP: 22° F
 LIQUID STUB: 3/8IN ODS
 SUCTION STUB: 1/2IN ODS

ELECTRICAL 115VAC, 60HZ, 1PH.
 EVAP. FANS: .52A
 TOTAL: .52A
 MCA: 15.0A

NOTES:

1. OPTIONS NOT SHOWN ON DRAWING SHOULD BE LISTED IN WRITTEN PROPOSAL AND LISTED ON PURCHASE ORDER.
2. ELEC. CONNECTION: 115V/230V, 4x4 SUPPLY BOX AS NEEDED.
3. EXPANSION VALVES: SPORLAN "Q" SERIES STANDARD UNLESS OTHERWISE SPECIFIED.
4. DEFROST CONTROL: REMOTE CASES (N/A, DIGITAL CASE CONTROLLERS AVAILABLE), OPTIONAL CONDENSING UNIT (DIGITAL CASE CONTROLLER).
5. THERMOSTATS & LIQUID LINE SOLENOID VALVES: OPTIONAL.
6. DRAIN: 1 1/2 INCH PVC.
7. SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.



| | | | | | | |
|------------------------|-------|--------------|---------------------------|---|------|------------------|
| AUTHORIZATION (PRINT): | DATE: | | |  börgeren systems | | DRAWN BY: D HUNT |
| SIGNATURE: | | 6-12-09 DRH | DATE: 6-17-08 | | | CHECKED BY: |
| | | 12-8-08 DRH | 12FT LPM FIELD OF FLOWERS | | | |
| | | 11-24-08 DRH | | | | |
| | | DATE | REV. | DIM: | INCH | DRAWING NUMBER |
| | | REVISION | TOL: | | | P5435 |