



**DOORED CASE SPECIFICATIONS:**

REFRIGERATION  
 LOAD: 6,900 BTU/hr  
 COIL TEMP: 22° F  
 LIQUID STUB: 3/8IN ODS  
 SUCTION STUB: 5/8IN ODS

ELECTRICAL 115VAC, 60HZ, 1PH.  
 EVAP. FANS: .26A  
 LIGHT BALLAST: 1.88A  
 TOTAL: 2.14A  
 MCA: 15.0A

**OPEN CASE SPECIFICATIONS:**

REFRIGERATION  
 LOAD: 8,750 BTU/hr  
 COIL TEMP: 22° F  
 LIQUID STUB: 3/8IN ODS  
 SUCTION STUB: 5/8IN ODS

ELECTRICAL 115VAC, 60HZ, 1PH.  
 EVAP. FANS: .39A  
 LIGHT BALLAST: .94A  
 FRESH WATER SYSTEM: 5.0A  
 TOTAL: 6.33A  
 MCA: 15.0A

**NOTES:**

1. OPTIONS NOT SHOWN ON DRAWING SHOULD BE LISTED IN WRITTEN PROPOSAL AND LISTED ON PURCHASE ORDER.
2. ELEC. CONNECTION: 115V/230V, 4x4 SUPPLY BOX AS NEEDED.
3. EXPANSION VALVES: SPORLAN "Q" SERIES STANDARD UNLESS OTHERWISE SPECIFIED.
4. DEFROST CONTROL: REMOTE CASES (N/A, DIGITAL CASE CONTROLLERS AVAILABLE), OPTIONAL CONDENSING UNIT (DIGITAL CASE CONTROLLER).
5. THERMOSTATS & LIQUID LINE SOLENOID VALVES: OPTIONAL.
6. DRAIN: 1 1/2 INCH PVC.
7. SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.

FLOOR DRAIN MUST BE PROVIDED FOR THIS CASE



AUTHORIZATION (PRINT):	DATE:			SCALE: 1:32	DRAWN BY: D. HUNT
SIGNATURE:				DATE: 7-2-09	CHECKED BY:
		7-6-09	DRH	4DR 6FT DF FWE	
DATE	REV	BY	INCH	DRAWING NUMBER	
REVISION	TOL			P5660	