

BOTTLE CAPACITY: 480


CASE SPECIFICATIONS:

REFRIGERATION  
 LOAD: 7,700 BTU/hr  
 COIL TEMP: 30° F  
 LIQUID STUB: 3/8IN ODS  
 SUCTION STUB: 5/8IN ODS

ELECTRICAL 115VAC, 60HZ, 1PH.  
 EVAP. FANS: .26A  
 LIGHT BALLAST: 2.82A  
 TOTAL: 3.08A  
 MCA: 15.0A

NOTES:

1. OPTIONS NOT SHOWN ON DRAWING SHOULD BE LISTED IN WRITTEN PROPOSAL AND LISTED ON PURCHASE ORDER.
2. ELEC. CONNECTION: 115V/230V, 4x4 SUPPLY BOX AS NEEDED.
3. EXPANSION VALVES: SPORLAN "Q" SERIES STANDARD UNLESS OTHERWISE SPECIFIED.
4. DEFROST CONTROL: REMOTE CASES (N/A, DIGITAL CASE CONTROLLERS AVAILABLE), OPTIONAL CONDENSING UNIT (DIGITAL CASE CONTROLLER).
5. THERMOSTATS & LIQUID LINE SOLENOID VALVES: OPTIONAL.
6. DRAIN: 1 1/2 INCH PVC.
7. SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.

|                        |       |   |               |                  |
|------------------------|-------|---|---------------|------------------|
| AUTHORIZATION (PRINT): | DATE: |  <b>börger systems</b> |               | DRAWN BY: D HUNT |
| SIGNATURE:             |       |   |               | SCALE: 1:24      |
|                        |       | DATE: 10-22-09  | 6FT OPEN WINE |                  |
| DATE                   | REV   | BY  | INCH          | DRAWING NUMBER   |
| REVISION               |       | TOL   |               | P5718            |