

CASE SPECIFICATIONS:

TOP AREA: 111.3 SQR FT

REFRIGERATION LOAD: 13,830 BTU/hr
 COIL: CTA 46-140
 SUCTION TEMP: 22° F
 LIQUID: 3/8IN ODS
 SUCTION: 7/8IN ODS


ELECTRICAL 115VAC, 60HZ, 1PH.
 EVAP. FANS: 4.4A
 TROFFER LIGHTS: 3.76A
 TOTAL: 8.16A
 MCA: 15.0A

REMOTELY LOCATED CONDENSING UNIT
 ELECTRICAL 208-230VAC, 60HZ, 1PH.
 2HP COND. UNIT: 10.9A
 TOTAL: 10.9A
 MCA: 16.5A

NOTES:

1. OPTIONS NOT SHOWN ON DRAWING SHOULD BE LISTED IN WRITTEN PROPOSAL AND LISTED ON PURCHASE ORDER.
2. ELEC. CONNECTION: 115V/230V, 4x4 SUPPLY BOX AS NEEDED.
3. EXPANSION VALVES: SPORLAN "Q" SERIES STANDARD UNLESS OTHERWISE SPECIFIED.
4. DEFROST CONTROL: REMOTE CASES (N/A, DIGITAL CASE CONTROLLERS AVAILABLE), OPTIONAL CONDENSING UNIT (DIGITAL CASE CONTROLLER).
5. THERMOSTATS & LIQUID LINE SOLENOID VALVES: OPTIONAL.
6. DRAIN: 1 1/2 INCH PVC.
7. SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.



AUTHORIZATION (PRINT):		DATE:		 börger systems	
SIGNATURE:					
				DATE: 9-12-08	CHECKED BY:
				2 BTD CSRV	
DATE	REV	DRW	INCH	DRAWING NUMBER	
REVISION	TOL:			P5487A	