





CASE SPECIFICATIONS:

TOP AREA: 127.0 SQR FT

REFRIGERATION LOAD: 17,500 BTU/hr

COIL: CTA 46-190

SUCTION TEMP: 22° F

LIQUID STUB: 3/8IN ODS

SUCTION STUB: 7/8IN ODS

ELECTRICAL 115VAC, 60HZ, 1PH.

EVAP. FANS: 4.4A

TOTAL: 4.4A

MCA: 15.0A

NOTES:

1. OPTIONS NOT SHOWN ON DRAWING SHOULD BE LISTED IN WRITTEN PROPOSAL AND LISTED ON PURCHASE ORDER.
2. ELEC. CONNECTION: 115V/230V, 4x4 SUPPLY BOX AS NEEDED.
3. EXPANSION VALVES: SPORLAN "Q" SERIES STANDARD UNLESS OTHERWISE SPECIFIED.
4. DEFROST CONTROL: REMOTE CASES (N/A, DIGITAL CASE CONTROLS AVAILABLE), OPTIONAL CONDENSING UNIT (DIGITAL CASE CONTROLLER).
5. THERMOSTATS & LIQUID LINE SOLENOID VALVES: OPTIONAL.
6. DRAIN: 1 1/2 INCH PVC.
7. SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.

AUTHORIZATION (PRINT):		DATE:		 börger systems	
SIGNATURE:					
		SCALE: 1:48	DRAWN BY: D HUNT		
		DATE: 2-26-09	CHECKED BY:		
		2 BTD CSRV			
DATE	REV	BY	INCH	DRAWING NUMBER	
REVISION	TOL			P5600	