



CASE SPECIFICATIONS (BOTTOM):

REFRIGERATION:
 LOAD: 4,320 BTU/hr
 SUCTION TEMP: 20°F
 SUCTION LINE: 5/8IN ODS
 LIQUID LINE: 3/8IN ODS

ELECTRICAL 115V, 60HZ, 1PH
 EVAP. FANS: 0.13A
 LIGHT BALLASTS: 0.74A
 TOTAL: 0.87A

CASE SPECIFICATIONS (DOORS):

REFRIGERATION:
 LOAD: 1,350 BTU/hr
 SUCTION TEMP: 20°F
 SUCTION LINE: 5/8IN ODS
 LIQUID LINE: 3/8IN ODS

ELECTRICAL 115V, 60HZ, 1PH
 EVAP. FANS: .35A
 LIGHT BALLASTS: 0.74A
 TOTAL: 1.09A

NOTES:

1. OPTIONS NOT SHOWN ON DRAWING SHOULD BE STATED IN WRITTEN PROPOSAL AND LISTED ON PURCHASE ORDER.
2. ELEC. CONNECTION: 115V/230V, 4X4 SUPPLY BOX AS NEEDED.
3. EXPANSION VALVES: SPORLAN "Q" SERIES STANDARD UNLESS OTHERWISE SPECIFIED.
4. DEFROST CONTROL: REMOTE CASES (N/A, DIGITAL CASE CONTROLLERS AVAILABLE), OPTIONAL CONDENSING UNIT (DIGITAL CASE CONTROLLER).
5. THERMOSTATS & LIQUID LINE SOLENOID VALVES: OPTIONAL.
6. DRAIN: 1 INCH NATIONAL PIPE STRAIGHT THREAD.
7. SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.

| | | | |
|---------------------|----------|---|---------------------------------|
| | |  börger systems | |
| SCALE: | 1:16 | DRAWN BY: | D. HUNT |
| DATE: | 9-1-2000 | CHECKED BY: | NAME |
| 4' DOORS ABOVE OPEN | | | |
| DATE | REV. | CHK. | INCH |
| REVISION | | TOL: | ±1/32 |
| | | | DRAWING NUMBER P3560B |