

REFRIGERATION: COIL: CTA 38-98.

11,200 BTU/hr @ 20°F

1/2IN ODS LIQUID.

7/8IN ODS SUCTION.

TOP AREA: 70.3 SQR FEET.

ELECT. LOADS: 115V, 14.8A, 60HZ, 1PH.

ALL ELECT LOADS MAXIMUM AND INCLUDE THE FOLLOWING:

(4) FANS 4.4A, (4) MERCH. BALLASTS 9.6A,

(1) STORAGE BALLAST 0.80

WALKIN COOLER INFORMATION:

(1) LIGHT SWITCH ADJACENT SERVICE DOOR HANDLE.

(1) THERMOMETER ABOVE LIGHT SWITCH.

(1) VENT ABOVE THE SERVICE DOOR.

DISPLAY IN FORMATION:


(6) BACK PANELS ON THE DIVIDING WALL ARE HINGED FOR REAR STOCKING.

(18) TEMPERED GLASS SHELVES ARE HIEGHT ADJUSTABLE.

(1) WINDOW AT END OF THE DISPLAY AREA.

## NOTES:

1. OPTIONS NOT SHOWN ON DRAWING SHOULD BE LISTED IN WRITTEN PROPOSAL AND LISTED ON PURCHASE ORDER.
2. ELEC. CONNECTION: 115V/230V, 4x4 SUPPLY BOX AS NEEDED.
3. EXPANSION VALVES: SPORLAN "Q" SERIES STANDARD UNLESS OTHERWISE SPECIFIED.
4. DEFROST CONTROL: REMOTE CASES (N/A, DIGITAL CASE CONTROLLERS AVAILABLE), OPTIONAL CONDENSING UNIT (DIGITAL CASE CONTROLLER).
5. THERMOSTATS & LIQUID LINE SOLENOID VALVES: OPTIONAL.
6. DRAIN: 1 1/2 INCH PVC.
7. SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.

AUTHORIZATION (PRINT):		DATE:		 <b>börger systems</b>	
SIGNATURE:					
				SCALE: 1:32	DRAWN BY: D. HUNT
				DATE: 6-15-00	CHECKED BY:
		6DR WOD ARC			
DATE	REV.	DIM:	INCH	DRAWING NUMBER	
REVISION		TOL:		P3453A	