

CASE SPECIFICATIONS:

REFRIGERATION

LOAD: 4,600 BTU/hr  
 COIL TEMP: 25° F  
 LIQUID STUB: 3/8IN ODS  
 SUCTION STUB: 5/8IN ODS

ELECTRICAL 115VAC, 60HZ, 1PH.

EVAP. FANS: .60A  
 LIGHTS: 2.4A  
 CONDENSATE PUMP: 1.0A  
 EVAP. PAN: 3.0A  
 TOTAL: 7.0A  
 MCA: 15.0A


ELECTRICAL 230VAC, 60HZ, 1PH.

3/4HP COND. UNIT: 6.1A  
 TOTAL: 6.1A  
 MCA: 8.8A

NOTES:

1. OPTIONS NOT SHOWN ON DRAWING SHOULD BE LISTED IN WRITTEN PROPOSAL AND LISTED ON PURCHASE ORDER.
2. ELEC. CONNECTION: 115V/230V, 4x4 SUPPLY BOX AS NEEDED.
3. EXPANSION VALVES: SPORLAN "Q" SERIES STANDARD UNLESS OTHERWISE SPECIFIED.
4. DEFROST CONTROL: REMOTE CASES (N/A, DIGITAL CASE CONTROLLERS AVAILABLE), OPTIONAL CONDENSING UNIT (DIGITAL CASE CONTROLLER).
5. THERMOSTATS & LIQUID LINE SOLENOID VALVES: OPTIONAL.
6. DRAIN: 1 1/2 INCH PVC.
7. SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.



AUTHORIZATION (PRINT):		DATE:		 <b>börgeren systems</b>		DRAWN BY: D HUNT	
SIGNATURE:						CHECKED BY:	
				SCALE: 1:24			
				DATE: 9-12-94			
				3 DOOR 2 BAY			
		12-3-13 DRH					
		DATE REV. DIM. INCH					
		REVISION TOL:					
						DRAWING NUMBER P1508	