

CASE SPECIFICATIONS:

REFRIGERATION


LOAD: 4,025 BTU/hr
 SUCTION TEMP: 20° F
 LIQUID LINE: 3/8IN ODS
 SUCTION LINE: 5/8IN ODS

ELECTRICAL 115VAC, 60HZ, 1PH.
 EVAP. FANS: .13A
 LIGHT BALLAST: 1.48A
 CONDENSATE PUMP: 1.0A
 EVAP. PAN: 3.0A
 TOTAL: 5.61A

ELECTRICAL 230VAC, 60HZ, 1PH.
 3/4HP COND. UNIT: 6.1A
 TOTAL: 6.1A
 MCA: 8.8A

NOTES:

1. OPTIONS NOT SHOWN ON DRAWING SHOULD BE LISTED IN WRITTEN PROPOSAL AND LISTED ON PURCHASE ORDER.
2. ELEC. CONNECTION: 115V/230V, 4x4 SUPPLY BOX AS NEEDED.
3. EXPANSION VALVES: SPORLAN "Q" SERIES STANDARD UNLESS OTHERWISE SPECIFIED.
4. DEFROST CONTROL: REMOTE CASES (N/A, DIGITAL CASE CONTROLLERS AVAILABLE), OPTIONAL CONDENSING UNIT (DIGITAL CASE CONTROLLER).
5. THERMOSTATS & LIQUID LINE SOLENOID VALVES: OPTIONAL.
6. DRAIN: 1 INCH NATIONAL PIPE STRAIGHT THREAD.
7. SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.

				börger systems	
		SCALE: 1:12			DRAWN BY: J MAUK
6-15-04	DRH	DATE: 6-27-96			CHECKED BY:
4-19-02	DRH	3 DOOR			
6-3-98	JMM				
DATE	REV.	DIM:	INCH	DRAWING NUMBER	
REVISION	TOL:			P2260B	